Declaration of Performance



Exzellent STP 520

Reference number of the Declaration of Performance: IN4184070

1.	Unique ID code of the product type	Exzellent STP 520		
2.	Application(s)	Normal plastering mortar (in- and outdoor) for sustainable moisture regulation of wet and salt-loaded surfaces		
3.	Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany		
4.	Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany		
5.	System of AVCP	System 4		
6.	Harmonised standard	DIN EN 998-1: 2010		
7.	Notified body	-		

8. Declared performances

Essential characteristic	Performance	AVCP	harmonised technical specification
Water absorption	W0	System 4	DIN EN 998-1: 2010
Water vapour permeability	µ ≤ 20		
Tensile strength	≥ 0.7 N/mm² Fracture appearance B		
Thermal conductivity	0.67 W/m x K (tabular value)		
Durability (frost resistance)	Evaluation dependant on the determinations at the intended production site of the render.		
Fire behaviour	A1	-	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality



Bottrop, 16.03.2024 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.