

Mycoflex 488 MS

Reference number of the Declaration of Performance: CC9230XXX

| | |
|---------------------------------------|---|
| 1. Unique ID code of the product type | Mycoflex 488 MS |
| 2. Application(s) | Sealants for facade for interior and exterior application (intended for use in cold climates) Trass-lime mortar for masonry and renders Anchorage product |
| 3. Manufacturer | MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany |
| 4. Authorized representative | - |
| 5. System of AVCP | System 3 System 3 (for fire behaviour only) |
| 6. Harmonised standard | DIN EN 15651-1: 2012 DIN EN 15651-4: 2012 |
| 7. Notified body | KIWA Deutschland GmbH ID code NB 1119 |

8. Declared performances


| Essential characteristic | Performance | harmonised technical specification |
|---|--------------|------------------------------------|
| Stability | ≤ 3 mm | DIN EN 15651-1: 2012 |
| Loss of volume | ≤ 10 % | |
| Tensile behaviour for non-bearing sealants with high modulus | ≤ 0.9 MPa | |
| Durability | passed | |
| Release of chemicals dangerous to the environment and health | rated | |
| Fire behaviour | E | |
| Tensile behaviour (i.e. under preload) | passed | DIN EN 15651-4: 2012 |
| Loss of volume | ≤ 10 % | |
| Ultimate fracture strength | passed | |
| Adhesion/stretching behaviour under preload after 28-day water storage | passed | |
| Adhesion/stretching behaviour under preload after 28-day salt water storage | passed | |
| Tensile properties (i.e. secant modulus) at -30°C | ≤ 0.9 MPa | |
| Tensile behaviour under preload at -30°C | passed | |
| Durability | passed | |
| Release of chemicals dangerous to the environment and health | not required | |

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



(signature)

The image shows a blue ink signature over a circular stamp. The stamp contains the text 'LEISTUNGSEKLÄRUNG' at the top, 'CE' in the center, and 'DECLARATION OF PERFORMANCE' at the bottom. The MC logo is also present on the right side of the stamp.

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.