



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-AnchorSolid E820 - Komponente A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Application of the substance / the mixture

Epoxy coating
Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS09

Signal word

Danger

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 1)

· **Hazard-determining components of labelling:**

epoxide derivates
methyl toluene-4-sulphonate
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]
dioxirane
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane
(1:2)
Polyol epoxy hybrid
oxirane, 2-(chloromethyl)-, polymer with α -hydro- ω -
hydroxypoly[oxy(methyl-1,2-ethanediyl)]

· **Hazard statements**

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all
contaminated clothing. Rinse skin with water [or
shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for
several minutes. Remove contact lenses, if
present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it
before reuse.

· **Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic
reaction.
EUH211 Warning! Hazardous respirable droplets may be formed
when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:**

Resin mixture with colouring agents.
Mixture consisting of the following components.

(Contd. on page 3)

GB



BE SURE. BUILD SURE.

Page 3/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name **MC-AnchorSolid E820 - Komponente A**

(Contd. of page 2)

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	30-60%
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
CAS: 80-48-8 EINECS: 201-283-5	methyl toluene-4-sulphonate Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥5-<10%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥2.5-<10%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥1-<5%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<2.5%
	Polyol epoxy hybrid Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH205	≥0.1-<1%
CAS: 9072-62-2	oxirane, 2-(chloromethyl)-, polymer with α-hydro-ω-hydroxypoly[oxy(methyl-1,2-ethanediyl)] Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥0.1-<0.5%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 3)

- **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case product reaches water or sewage system.
Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Open and handle containers with care.
Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.
are required.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 4)

skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** None.
- **Storage class** 8A

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Keep away from food, drink and animal feed. Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin.
- **Breathing equipment:** If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection** Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf> For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 5)

can be found under point 8 "Penetration time of the glove material".
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· Eye/face protection

Tight-fitting safety goggles.

Safety goggles.

· Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Colour:**

White

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

>200 °C

· **Flash point:**

>100 °C

· **Auto-ignition temperature:**

184 °C

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

110000 mPas

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 6)

<ul style="list-style-type: none"> · Solubility · Water: Not miscible or difficult to mix · Steam pressure at 20 °C: 0.1 hPa · Density and/or relative density · Density at 20 °C 1.5 g/cm³
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible.
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> · 10.1 Reactivity No further relevant information available. · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. · 10.3 Possibility of hazardous reactions No dangerous reactions known · 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.
--

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 7)

· **10.6 Hazardous decomposition products:** Possible in traces.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 epoxide derivatives

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

CAS: 80-48-8 methyl toluene-4-sulphonate

Oral	LD50	341 mg/kg (rat)
------	------	-----------------

CAS: 13463-67-7 titanium dioxide

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>10000 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4 h	>6.8 mg/l (rat)
------------	----------	-----------------

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	LD50	8030 mg/kg (rat)
------	------	------------------

Dermal	LD50	4248 mg/kg (rabbit)
--------	------	---------------------

Polyol epoxy hybrid

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

· **Skin corrosion/irritation** Causes severe skin burns and eye damage.

· **Serious eye damage/irritation** Causes serious eye damage.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

CB

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 1675-54-3 epoxide derivates

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

Polyol epoxy hybrid

LC50/96h	67 mg/l (Leucidus idus)
EC50/48h	90 mg/l (Daphnia magna)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

Toxic for fish

Additional ecological information:

General notes:

Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR, IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates), MARINE POLLUTANT

14.3 Transport hazard class(es)

ADR
Class 9 (M6) Miscellaneous dangerous substances and articles.
Label 9

IMDG, IATA

Class 9 Miscellaneous dangerous substances and articles.
Label 9

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: Yes
Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)
Special marking (IATA): Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.
Kemler Number: 90
EMS Number: F-A, S-F
Stowage Category A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

(-)

· Remarks:

1 kg: LQ

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 26 (replaces version 25)

Revision: 16.03.2024

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 11)

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

Department issuing data specification sheet:

Environment protection department.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.