



BE SURE. BUILD SURE.

Page 1/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

##### Trade name

**MC-DUR TopSpeed flex plus - Komponente A**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

##### Product category

PC9a Coatings and paints, thinners, paint removers

##### Process category

PROC10 Roller application or brushing

##### Environmental release category

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC11a Widespread use of articles with low release (indoor)

##### Article category

AC13 Plastic articles

##### Application of the substance / the mixture

Schwimmschicht

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

##### Informing department:

msds@mc-bauchemie.de

##### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

**Trade name MC-DUR TopSpeed flex plus - Komponente A**

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:** *tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate 4-morpholinecarbaldehyde*
- **Hazard statements** *H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.*
- **Precautionary statements** *P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Additional information:** *EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** *Resin mixture.  
Mixture consisting of the following components.*

· **Dangerous components:**

CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64-xxxx	<i>tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate</i> <i>Skin Sens. 1, H317; Aquatic Chronic 3, H412</i>	50-70%
CAS: 13463-67-7 EINECS: 236-675-5	<i>titanium dioxide</i> <i>Carc. 2, H351</i>	≥1-<10%
CAS: 222417-26-7	<i>Polyacrylate</i> <i>Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315</i>	≥0.25-<0.5%
CAS: 4394-85-8 EINECS: 224-518-3 Reg.nr.: 01-2119987993-12	<i>4-morpholinecarbaldehyde</i> <i>Skin Sens. 1, H317</i>	≥0.1-<0.5%

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information** *Remove soiled, soaked clothing immediately.*
- **After inhalation** *Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.*

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex plus - Komponente A

(Contd. of page 2)

- **After skin contact** *In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.*
- **After eye contact** *Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.*
- **After swallowing** *Do NOT induce vomiting. Rinse mouth with water. Medical attention required.*
- **4.2 Most important symptoms and effects, both acute and delayed** *Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.*
- **4.3 Indication of any immediate medical attention and special treatment needed** *Therapeutic measures: No information available.*

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *No special measures required.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *No dangerous materials are released.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be*

(Contd. on page 4)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

**Trade name MC-DUR TopSpeed flex plus - Komponente A**

(Contd. of page 3)

used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required.

The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

**Information about protection against explosions and fires:**

Keep ignition sources away - do not smoke.  
Protect from heat.  
Do not store near heat sources.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

**Storage**

**Requirements to be met by storerooms and containers:**

Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.

Storage temperature >5°C and <30°C

**Information about storage in one common storage facility:**

May be stored together with hazardous substances of other classes up to 200 kg.

**Further information about storage conditions:**

Keep container tightly closed in a well-ventilated place.

**Storage class**

10

**7.3 Specific end use(s)**

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Components with critical values that require**

**monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**DNELs**

**CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

Dermal DNEL 4 mg/kg bw/day (ArL)

Inhalative DNEL 28 mg/m<sup>3</sup> (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

**Trade name MC-DUR TopSpeed flex plus - Komponente A**

(Contd. of page 4)

	112 mg/m <sup>3</sup> (Ark)
--	-----------------------------

**· PNECs**

**CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

PNEC	31.1 mg/l (Kla)
	0.000013 mg/l (Mew)
	0.00013 mg/l (Freshwater)
PNEC	0.1 mg/kg dwt (Bod)
	0.02 mg/kg dwt (Marine water sediment)
	0.21 mg/kg dwt (Fresh water sediment)

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· 8.2 Exposure controls**

**· Appropriate engineering controls**

No further data; see section 7.

**· Individual protection measures, such as personal protective equipment**

**· General protective and hygienic measures**

Do not smoke, eat or drink while working. Have eye wash equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Do not store food in the work area. Wash hands before breaks and at the end of work.

**· Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

**· Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluororubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Multi-layer glove - PE/EVAL/PE ; Breakthrough time  $\geq 480\text{ min}$ .

Recommendation: Dispose of contaminated gloves.

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**· Penetration time of glove material**

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluoro rubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Multi-layer glove - PE/EVAL/PE ; Breakthrough time  $\geq 480\text{ min}$ .

**· Eye/face protection**

Wear safety goggles/face protection.

**· Body protection:**

Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not recommended.



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex plus - Komponente A

(Contd. of page 5)

#### SECTION 9: Physical and chemical properties

##### 9.1 Information on basic physical and chemical properties

###### General Information

· <b>Colour:</b>	According to product specification
· <b>Smell:</b>	Product specific
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	209 °C (CAS: 152637-10-0 poly(oxy(methyl-1,2-ethanediyl)))
· <b>Flash point:</b>	93 °C
· <b>Auto-ignition temperature:</b>	300 °C (CAS: 1761-71-3 4,4'-methylenebis(cyclohexan-1-amine))
· <b>pH</b>	Not applicable. Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>dynamic at 20 °C:</b>	1500 mPas
· <b>Solubility</b>	
· <b>Water:</b>	Not miscible or difficult to mix
· <b>Steam pressure at 20 °C:</b>	54.9 hPa (CAS: 1761-71-3 4,4'-methylenebis(cyclohexan-1-amine))
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.42 g/cm <sup>3</sup>

##### 9.2 Other information

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.

##### Information with regard to physical hazard classes

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex plus - Komponente A

(Contd. of page 6)

- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

#### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

#### SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

**CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)

Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

**CAS: 13463-67-7 titanium dioxide**

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >10000 mg/kg (rabbit)

Inhalative LC50/4 h >6.8 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

**Trade name MC-DUR TopSpeed flex plus - Komponente A**

(Contd. of page 7)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

LC50/96h	66 mg/l (Danio rerio) (OECD 203)
EC50	3110 mg/l (BEL)
EC50/48h	88.6 mg/l (Daphnia magna)
NOEC	0.01 mg/l (Daphnia magna)
ErC50/72h	113 mg/l (Scenedesmus subspicatus)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

GB

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex plus - Komponente A

(Contd. of page 8)

#### SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· UN "Model Regulation":	Void

#### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture  
No further relevant information available.

· Poisons Act

· Regulated explosives precursors

CAS: 7664-38-2	phosphoric acid	30%
----------------	-----------------	-----

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 24 (replaces version 23)

Revision: 12.04.2024

**Trade name MC-DUR TopSpeed flex plus - Komponente A**

(Contd. of page 9)

· **Relevant phrases**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H351 Suspected of causing cancer.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data  
specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the  
previous version altered.**

GB