



BE SURE. BUILD SURE.

Page 1/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Nafuflex Profi Tech 1**

Article number: 3151

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Bitumen high build coating

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS07

##### Signal word

Warning

##### Hazard-determining

##### components of labelling:

2-methyl-2H-isothiazol-3-one  
2-octyl-2H-isothiazol-3-one

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 1)

- **Hazard statements**  
Rosin  
8-cyclohexadecen-1-one  
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**  
Contains biocidal products: 8-cyclohexadecen-1-one, 2-methyl-2H-isothiazol-3-one, 2-octyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 8052-42-4 EINECS: 232-490-9	Asphalt substance with a Community workplace exposure limit	30-60%
CAS: 8050-09-7 EINECS: 232-475-7	Rosin Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 1314-13-2 EINECS: 215-222-5	Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<0.5%

(Contd. on page 3)

GB



BE SURE. BUILD SURE.

Page 3/13

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 2)		
CAS: 1219010-04-4 EC number: 629-719-3 Reg.nr.: 01-2119487014-41	<i>N-C16-18 (even numbered) and C18 (unsaturated) alkyl propane-1,3-diamine</i> STOT RE 1, H372; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302	<0.025%
CAS: 2634-33-5	<i>8-cyclohexadecen-1-one</i> Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317:C ≥ 0.05 %	<0.025%
CAS: 2682-20-4 EINECS: 220-239-6	<i>2-methyl-2H-isothiazol-3-one</i> Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0015-<0.025%
CAS: 13463-41-7 EINECS: 236-671-3	<i>pyrithione zinc</i> Acute Tox. 3, H301; Acute Tox. 2, H330; Repr. 1B, H360D; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10) ATE: LD50 oral: 221 mg/kg LC50/4 h inhalative: 0.14 mg/l	≥0.0025-<0.025%

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 3)

<p>CAS: 26530-20-1 EINECS: 247-761-7</p>	<p>2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A;H317: C ≥ 0.0015 %</p>	<p>≥0.0015-&lt;0.0025%</p>
<p>CAS: 55965-84-9</p>	<p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C &lt; 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C &lt; 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %</p>	<p>&lt;0.00025%</p>

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information** No special measures required.
- **After inhalation** Supply fresh air.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** Rinse out mouth and then drink plenty of water. Seek medical treatment.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB



BE SURE. BUILD SURE.

Page 5/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

Trade name Nafuflex Profi Tech 1

(Contd. of page 4)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** No dangerous materials are released.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class** 12
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

Trade name Nafuflex Profi Tech 1

(Contd. of page 5)

#### SECTION 8: Exposure controls/personal protection

##### 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 8052-42-4 Asphalt

WEL Short-term value: 10 mg/m<sup>3</sup>  
Long-term value: 5 mg/m<sup>3</sup>

CAS: 8050-09-7 Rosin

WEL Short-term value: 0.15 mg/m<sup>3</sup>  
Long-term value: 0.05 mg/m<sup>3</sup>  
Sen

Additional information: The lists that were valid during the compilation were used as basis.

##### 8.2 Exposure controls

Appropriate engineering controls

No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Breathing equipment:

Only during spraying without adequate removal by suction.  
Short term filter device:  
Filter A/P2.

Hand protection

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

Material of gloves

Nitrile rubber, NBR  
Butyl rubber, BR

Penetration time of glove material

The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.

Eye/face protection

Safety glasses

#### SECTION 9: Physical and chemical properties

##### 9.1 Information on basic physical and chemical properties

General Information

Colour:

Dark brown

Smell:

neutral

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

100 °C (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)

Flash point:

Not applicable

pH at 20 °C

9

Viscosity:

Kinematic viscosity

Not determined.

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

Trade name Nafuflex Profi Tech 1

(Contd. of page 6)

- **dynamic at 20 °C:** 20000 mPas
- **Solubility**
- **Water:** Fully miscible
- **Steam pressure at 20 °C:** 23 hPa (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
- **Density and/or relative density**
- **Density at 20 °C** 1.03 g/cm<sup>3</sup>

- **9.2 Other information**
- **Appearance:**
- **Form:** Viscous
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

#### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 7)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**  
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**CAS: 8052-42-4 Asphalt**

Dermal	LD50	>2000 mg/kg (rabbit)
	NOAEL	2000 mg/kg (rabbit)
Inhalative	NOAEL	103.9 mg/l (rat)

**CAS: 8050-09-7 Rosin**

Oral	LD50	>2500 mg/kg (Meerschweinchen)
		>3000 mg/kg (mouse)
		>2000 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

**CAS: 1219010-04-4 N-C16-18 (even numbered) and C18 (unsaturated) alkyl propane-1,3-diamine**

Oral	LD50	500 mg/kg (rat)
	NOAEL	0.4 mg/kg (rat)

**CAS: 2634-33-5 8-cyclohexadecen-1-one**

Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

**CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one**

Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)

**CAS: 13463-41-7 pyrithione zinc**

Oral	LD50	221 mg/kg (ATE)
Inhalative	LC50/4 h	0.14 mg/l (ATE)

**CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one**

Oral	LD50	125 mg/kg (ATE)
		500 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE)
		>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.27 mg/l (ATE)
		0.6 mg/l (rat)

**CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

Oral	LD50	49.6-75 mg/kg (rat)
------	------	---------------------

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 8)

Dermal	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· <b>Endocrine disrupting properties</b>
None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 8052-42-4 Asphalt**

EC50/72h	>1000 mg/l (algae)
LC50/96h	0.002 mg/l (Coregonus clupeaformis)
	>1000 mg/l (fish)
EC50	0.062 mg/l (Gammarus pseudolimnaeus)
LC50/48h	>1000 mg/l (Daphnien)
NOEC	>1000 mg/l (Daphnien)

**CAS: 8050-09-7 Rosin**

EC50/48h	>1000 mg/l (Daphnia magna)
----------	----------------------------

**CAS: 1219010-04-4 N-C16-18 (even numbered) and C18 (unsaturated) alkyl propane-1,3-diamine**

LC50/24h	0.148 mg/l (fish)
EC50	0.29 mg/l (Daphnia magna)
NOEC	>0.01 mg/l (algae)

**CAS: 2634-33-5 8-cyclohexadecen-1-one**

EC50/72h	0.067 mg/l (Pseudokirchneriella subcapitata)
	0.11 mg/l (Selenastrum capricornutum)
LC50/96h	1.6 mg/l (Oncorhynchus mykiss)
EC50/48h	1.1 mg/l (Daphnia magna)

**CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one**

EC50/72h	0.157 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	6 mg/l (Oncorhynchus mykiss)

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 9)

EC50/48h	1.68 mg/l (Daphnies)
<b>CAS: 13463-41-7 pyrithione zinc</b>	
IC50/72h	0.067 mg/l (Senastrum capricornutum)
LC50/96h	0.15 mg/l (Oncorhynchus mykiss)
EC50/48h	0.05 mg/l (Daphnies)
<b>CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one</b>	
EC50/48h	0.42 mg/l (Daphnien)
<b>CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</b>	
LC50/24h	0.19 mg/l (fish)
EC50/72h	0.027 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	0.19 mg/l (Oncorhynchus mykiss)
LC50/48h	0.28 mg/l (fish)
EC50/48h	0.16 mg/l (Daphnia magna)
NOEC	0.02 mg/l (Oncorhynchus mykiss)
	0.00049 mg/l (Ske)
	0.1 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *The product does not contain substances with endocrine disrupting properties.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Danger to drinking water if even extremely small quantities leak into soil.*

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 10)

· **Recommended cleaning agent:**

Water, if necessary with cleaning agent.

#### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

Not dangerous according to the above specifications.

· **UN "Model Regulation":**

Void

#### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

CAS: 1310-73-2 sodium hydroxide

12% of total caustic alkalinity

CAS: 1336-21-6 ammonia

10%

(Contd. on page 12)



BE SURE. BUILD SURE.

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

Trade name Nafuflex Profi Tech 1

(Contd. of page 11)

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- ATE: Acute toxicity estimate values
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2
- Skin Corr. 1: Skin corrosion/irritation – Category 1
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 15.12.2023

Version number 31 (replaces version 30)

Revision: 15.12.2023

**Trade name Nafuflex Profi Tech 1**

(Contd. of page 12)

*Repr. 1B: Reproductive toxicity – Category 1B*

*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**· \* Data compared to the  
previous version altered.**

GB